

What is claimed is:

1. A magnetically navigable endoscope system comprising:
an endoscope having a proximal end and a distal end, the distal end having a magnetic
body;
an imaging device which transmits an image, associated with the distal end;
5 a display component for displaying the image;
a magnetic field generating apparatus for generating a magnetic field to move the
magnetic body and thus the distal end of the endoscope;
a controller coordinated with the display for controlling the magnetic field generating
apparatus to apply a magnetic field to change the position of the magnetic body and thus the
10 position of the distal end of the endoscope.

2. The magnetically navigable endoscope system according to claim 1 wherein
the controller controls the magnetic field generating apparatus to apply a magnetic field of a
specific direction to change the orientation of the magnetic body and thus the orientation of
the distal end of the endoscope.

3. The magnetically navigable endoscope system according to claim 1 wherein
the controller controls the magnetic field generating apparatus to apply a magnetic gradient to
move the magnetic body and thus the location of the distal end of the endoscope.

4. The magnetically navigable endoscope system according to claim 1 wherein
the controller controls the magnetic field generating apparatus to apply a magnetic field and a
20 magnetic gradient to apply a magnetic field of a specific direction to change the orientation of
the magnetic body and to apply a magnetic gradient to move the magnetic body and thus the
orientation and location of the distal end of the endoscope.

5. The magnetically navigable endoscope system according to claim 1 wherein the
controller is on the endoscope, adjacent the proximal end.

6. The magnetically navigable endoscope system according to claim 1 wherein the
controller is operable in at least two mutually perpendicular directions, movement in which
causes the magnetic field generating apparatus to change the magnetic field to move the distal
end of the endoscope in two mutually perpendicular directions.

7. The magnetically navigable endoscope system according to claim 1 wherein the
display includes indicia indicating an orientation of the displayed image, and wherein the
controller is operable in at least two mutually perpendicular directions, and movement in the

66740" 9602660

first direction causes the magnetic field generating apparatus to change the magnetic field to
5 move the distal end of the endoscope in a first plane relative to the indicia, and movement in
the second direction causes the magnetic field generating apparatus to change the magnetic
field to move the distal end of the endoscope in a second plane, perpendicular to the first
place.

8. The magnetically navigable endoscope system according to claim 7 wherein the
first plane is aligned with the indicia.

9. The magnetically navigable endoscope system according to claim 6, wherein the
display has vertical and horizontal directions, and wherein the movement of the controller in
one of the mutually perpendicular directions causes the magnetic field generating apparatus
to change the magnetic field to move the distal end of the endoscope in the vertical direction
5 as displayed on the display, and wherein the movement of the controller in the other of the
mutually perpendicular direction causes the magnetic field generating apparatus to change the
magnetic field to move the distal end of the endoscope in the horizontal direction as
displayed on the display.

10. The magnetically navigable endoscope system according to claim 9 further
comprising a signal processor orienting the image on the display so that the vertically "up"
direction of the image is oriented at the top of the display regardless of the actual orientation
of the axis of the endoscope.

11. The magnet assembly according to claim 1 wherein the endoscope includes a
magnet channel, and wherein there is at least one magnet body disposed in the magnet
channel adjacent the distal end.

12. The magnet assembly according to claim 1 wherein there are a plurality of
magnet bodies in the distal end portion of the endoscope.

13. The magnet assembly according to claim 1 wherein the magnet body
comprises a permanent magnetic material.

14. The magnet assembly according to claim 1 wherein the magnet body
comprises a permeable magnetic material.

15. A magnetically navigable endoscope system comprising:

661110" 3022220

an endoscope having a proximal end and a distal end, the distal end having a magnetic body;

a component which transmits an image, associated with the distal end;

5 a two-dimensional display for displaying the image from the image-transmitting component, the display having a vertical and horizontal direction;

a magnetic field generating apparatus for generating a magnetic field to orient the magnetic body and thus the distal end of the endoscope;

10 a controller for controlling the magnetic field generating apparatus to selectively apply to apply a magnetic field to change the position of the magnetic body and thus the position of the distal end of the endoscope, the controller operable in at least two mutually perpendicular directions, movement of the controller in one of the mutually perpendicular directions causing the magnetic field generating apparatus to change the magnetic field to move the distal end of the endoscope in the vertical direction as displayed on the display, and
15 wherein the movement of the controller in the other of the mutually perpendicular direction causes the magnetic field generating apparatus to change the magnetic field to move the distal end of the endoscope in the horizontal direction as displayed on the display.

16. A method of magnetically navigating an endoscope, the method comprising displaying an image from the distal end of the endoscope on a display, the display including an orientation indicia; and

operating a controller to control the application of a magnetic field to the distal end of
5 the endoscope, the controller being operable in at least two mutually perpendicular directions, movement of the controller in one of the mutually perpendicular directions causing the magnetic field generating apparatus to apply a magnetic field to move the distal end of the endoscope in a first plane relative to the orientation indicia on the display, and wherein the movement of the controller in the other of the mutually perpendicular directions causes the
10 magnetic field generating apparatus to change the magnetic field to move the distal end of the endoscope in a second plane, perpendicular to the first plane.

17. A method of magnetically navigating an endoscope, the method comprising displaying an image from the distal end of the endoscope on a display

operating a controller to control the application of a magnetic field to the distal end of the endoscope, the controller being operable in at least two mutually perpendicular directions,

5 movement of the controller in one of the mutually perpendicular directions causing the
magnetic field generating apparatus to change the magnetic field to move the distal end of the
endoscope in the vertical direction as displayed on the display, and wherein the movement of
the controller in the other of the mutual perpendicular directions causes the magnetic field
generating apparatus to change the magnetic field to move the distal end of the endoscope in
10 the horizontal direction as displayed on the display.

18. A magnetically navigable endoscope system comprising:

an endoscope having a proximal end and a distal end, the distal end having a magnetic
body;

a component which transmits an image, associated with the distal end;

5 a two-dimensional display for displaying the image from the image-transmitting
component, the display having a vertical and horizontal direction;

a magnetic field generating apparatus for generating a magnetic field to move the
magnetic body and thus the distal end of the endoscope; and

10 a controller for identifying the volume over which to orient the endoscope and
controlling the magnetic field generating apparatus to selectively change the magnetic field to
change the orientation of the magnetic body and thus the distal end of the endoscope over the
specified volume.

19. A method of magnetically controlling an endoscope in body lumens and
cavities, the method comprising:

localizing the distal end of an endoscope;

registering the location of the distal end of the endoscope to a pre-operative image set

5 such as an MR or CT;

identifying a direction on the pre-operative image set; and

controlling the magnetic field generating apparatus to move the distal end of the
endoscope in the identified direction.

20. The method of magnetically controlling an endoscope according to claim 19
10 wherein the magnetic field generating apparatus generates a magnetic field in the identified
direction to orient the distal end of the endoscope in the identified direction.

21. The method of magnetically controlling an endoscope according to claim 19
wherein the magnetic field generating apparatus generates a magnetic field with a gradient in
the identified direction to advance the distal end of the endoscope in the identified direction.

15 22. The method of magnetically controlling an endoscope according to claim 19 wherein the magnetic field generating apparatus generates a magnetic field with a field direction and gradient in the identified direction to orient and advance the distal end of the endoscope in the identified direction.

20 23. A method of magnetically controlling an endoscope in body lumens and cavities, the method comprising:

 localizing the distal end of an endoscope;

 registering the location of the distal end of the endoscope to a pre-operative image set such as MR or CT;

 programming a volume over which to move the endoscope; and

25 controlling the magnetic field generating apparatus to move the distal end of the endoscope in the specified volume.

 24. A method of magnetically navigating an endoscope in a body lumen or cavity with an applied magnetic field, the method comprising:

 displaying an image from the distal end of the endoscope in an orientation relative to a directional control such that operation of the directional control in a selected direction relative to the displayed image causes the applied magnetic field to change to move the distal end of the endoscope in a corresponding direction on the display, and

 operating the directional control corresponding to the desired direction as displayed upon the displayed image to apply a magnetic field to move the distal end in the desired direction as displayed upon the displayed image.

10 25. The method according to claim 24 wherein operating the directional control applies a magnetic field in the selected direction to orient the distal end of the endoscope in the desired direction.

 26. The method according to claim 24 wherein operating the directional control applies a magnetic field with a gradient in the selected direction to advance the distal end of the endoscope in the desired direction.

 27. The method according to claim 24 wherein operating the directional control applies a magnetic field in a selected direction, and with a gradient in the selected direction to orient and advance the distal end of the endoscope in the desired direction.

20 28. The method according to claim 24 wherein the step of displaying an image includes periodically reorienting the image by

operating the directional control to change the applied magnetic field to move the distal end of the endoscope.

identifying the direction of movement of the distal end of the endoscope on the display; and

25 reorienting the image on the display so that the direction of movement caused by operating the control intuitively corresponds to the directions-on the displayed image.

29. The method according to claim 24 wherein the endoscope is navigated through one of the lungs, the urinary tract, or the gastrointestinal tract, brain, and heart.

30. A magnetically navigable endoscope system comprising:

an endoscope having a proximal end and a distal end, the distal end having a magnetic body;

an imaging device which transmits an image, associated with the distal end;

5 a plurality of sensors triggered by contact with the wall of a body lumen or cavity, distributed around the distal end;

a two-dimensional display for displaying the image from the imaging device , the display having a vertical and horizontal direction;

10 a magnetic field generating apparatus for generating a magnetic field to orient the magnetic body and thus the distal end of the endoscope;

a computer which monitors feedback of the wall contact sensors and adjusts the magnetic field generating apparatus to selectively modify the magnetic field to change the orientation of the magnetic body such that the endoscope is automatically positioned within the body lumen or cavity.

31. The system according to claim 30 wherein the computer that monitors the feedback of the wall contact sensors adjusts the magnetic field generating apparatus to selectively modify the magnetic field to position the endoscope in generally the center of the body lumen or cavity.

32. The system according to claim 30 wherein the computer that monitors the feedback of the wall contact sensors adjusts the magnetic field generating apparatus to selectively modify the magnetic field to position the endoscope generally adjacent a selected wall of the body lumen or cavity.

33. The system according to claim 30 further comprising an advancing mechanism for advancing the endoscope.

60440 9022250

5

39. The magnetically controllable endoscope according to claim 35 further comprising a binder in the endoscope, and wherein the regions of different flexibility are formed by selective leaching of the binder.